

KLEENCO PRODUCTS, INC.
• P.O. BOX 1786 • Bellevue, WA. 98009

TELEPHONE NUMBER Reg. Phone 206-641-8888

For Emergency Assitance
Call Infotrac (800) 535-5053

| 1 = SLIGHT | 0 = INSIGNIFICANT | \* = SEE SECTION IV

HAZARD RATING	FIRE /
4 = EXTREME	1 AREACTIVITY
3 = HIGH	) (KEACHVIII
2 = MODERATE	(
1 = SLIGHT TOXI	CITY
1 = SLIGHT 0 = INSIGNIFICANT	ODEOLAL
* - CEE CECTION IV	SPECIAL

## MATERIAL SAFETY DATA SHEET

PRODUCT NAME	DAT	TE ISSUED	04	-21-93	С	ODE	DOT HAZARD			
KLEEN-SWEEP - Wax	Ba	ase	PRE	EPARED B	Y Dal	e R. Silbaugh		017-0158	Not Regulated	
FORMULA Proprietary	(	CHEMICAL NAMES AND OR SYNONYMS  Powdered Cleaning Compound								
I-COM	I-COMPOSITIONAL INFORMATION/SARA III INFORMATION									
INGREDIENTS		CAS NUMBER	OCCI				VAF	VAPOR PRESSURE WEIGHT mm Hg @ TEMP PERCENT		
No toxic chemical(s) subject to the reporting require will be provided to a physician in the event of a me	 of section 313 of Tittle III and 40 CFR nergency.	342. <b>N</b>	IOTE: The pred	cise con	nposition of this mixt	ure is p	proprietary. A more c	omplete description		
II-PHYSICAL PROPERTY INFORMATION										
APPEARANCE and ODOR										
Sawdust like material  MELTING POINT		IC POINT		COATING	V O C			EVAPORATION	DATE	
Not Applicable	BOILING POINT  Not Applicable			COATING V.O.C.  Not Applicable			Notapplicable			
SOLUBILITY IN WATER SPECIFIC GRAVITY (Water Not applicable Not available				VAPOR DENSITY NotApplicable						
III-FIRE AND EXPLOSION HAZARD INFORMATION										
	AUTO	IGNITION TEMPERATURE	: I			ON LIMIT (%)			SION LIMIT (%)	
NotApplicable		Not Available		Not Applicable			Not Applicable			
EXTINGUISHING MEDIA  X FOAM X CO2 X DRY CHEMICAL X WATER SPRAY OTHER										
SPECIAL FIRE FIGHTING PROCEDURES For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment. This may include self-contained breathing apparatus to protect against the hazardous effects of normal products of combustion or oxygen deficiency. Read the entire MSDS.										
self-contained breathing apparatus to protect against the hazardous effects of normal products of combustion or oxygen deficiency. Read the entire MSDS.  UNUSUAL FIRE AND EXPLOSION HAZARDS Noneknown										
SHOUGHE THE THE ENTERSION THEMES MUNICINIUMI										
IV-HEALTH HAZARD INFORMATION										
THRESHOLD LIMIT VALUE ROUTE(S		X INHALATION See Health Hazards		X SKIN See	Health I	Hazards	)	( INGESTION See Health Ha:	zards	
HEALTH HAZARDS (Acute and Chronic) CHRONIC EFFECTS OF EXPOSURE: Nonereported. *See Section IX.										
CARCINOGENICITY: Not considered to be a carcinogen	NTP	IARC N	/lonog	ıraphs	Χ	OSHA Regulate	ed			
SIGNS AND SYMPTOMS OF EXPOSURE INHALATION: Vapors and/or aerosols which may be formed at elevated temperatures may be irritating to eyes and respiratory tract. EYE CONTACT: Irritating. SKIN CONTACT: Low order of toxicity. Components may be absorbed through skin to produce hemolytic anemia and kidney damage evidenced by paleness and possibly red coloration of the urine. Frequent or prolonged contact may irritate. May cause skin sensitization, an allergic reaction which becomes evident on reexposure to this material. SWALLOWING: Minimal toxicity.										
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE None reported										
EMERGENCY AND FIRST AID PROCEDURES EYES: If this chemical contacts the eyes, immediately wash the eyes with large amounts of water and continue flushing for 15 minutes, occasionally lifting the lower and upper lids. Get medical attention if irritation occurs. Contact lenses should not be worn when working with this chemical. SKIN: If this chemical contacts the skin, flush the contaminated skin with water promptly. If this chemical penetrates the clothing, immediately remove the clothing and flush the skin with water promptly. Follow by washing with soap and water. If irritation persists after washing, get medical attention. INHALATION: If a person breathes large amounts of this chemical, move the exposed person to fresh air at once. If breathing has stopped, perform mouth-to-mouth resuscitation. Keep the affected person warm and at rest. Get medical attention as soon as possible. INGESTION: If this chemical has been swallowed, get medical										

----

V-REACTIVITY INFORMATION							
X STABLE UNSTABLE CONDITIONS TO AVOID Heat and open flame.							
HAZARDOUS DECOMPOSITION PRODUCTS Thermal decomposition products are highly dependent on the combustion conditions. A complex mixture of airborne solid, liquid particulates and gases will evolve when this material undergoes pyrolysis or combustion. Carbon monoxide and other unidentified organic compounds may be formed upon combustion.							
HAZARDOUS MAY WILL NOT CONDITIONS TO AVOID							
POLYMERZATION OCCUR Notapplicable.  NCOMPATIBILITY (Materials to avoid) Avoid heat, open flames, and oxidizing materials.							
VI-SPILL OR LEAK PROCEDURE INFORMATION							
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED Stop the source of leak or release. Clean up releases as soon as possible, observing precautions in Special Protective Information. Contain liquid to prevent further contamination of soil, surface water or groundwater. Clean up small spills using appropriate techniques such as sorbent materials or pumping. Where feasible and appropriate, remove contaminated soil. Follow prescribed procedures for reporting and responding to larger releases.							
WASTE DISPOSAL METHODS Place contaminated materials in disposable containers and dispose of in a manner consistent with applicable regulations. Contact local environmental authorities for approved disposal of this material. Components of this material are listed of the TSCA Inventory.							
VII-SPECIAL PROTECTION INFORMATION							
VENTILATION TYPE Local mechanical exhaust ventilation, capable of maintaining emissions at the point of use below the PEL.							
RESPIRATORY PROTECTION Wear a NIOSH-Approved respirator, appropriate for the concentration of vapor or mist encountered at the point of use.							
PROTECTIVE GLOVES Nitrile gloves EYE PROTECTION Wear eye protection to prevent any possibility of eye contact.							
DTHER PROTECTIVE EQUIPMENT Wear appropriate equipment to minimize skin contact.							
VIII-STORAGE AND HANDLING INFORMATION							
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE Keep out of reach of children. Store in a cool dry place away from incompatible materials. Keep container tightly closed when not in use. Workers should wash immediately when skin becomes contaminated and at the end of each work shift. The following equipment should be available: Eyewash. It is generally recognized that contact lenses should not be worn when working with chemicals because contact lenses may contribute to the severity of the injury.							
Read and follow label instructions. The label contains information necessary for the proper use of the product. Containers, even those that have been emptied, will retain product residue and vapors. Always obey hazard warnings and handle empty containers as if they were full.							
IX-TOXICITY INFORMATION							
This product contains ethylene glycol (<00.05%). Repeated high dose exposure to ethylene glycol by ingestion has caused kidney damage, brain damage, degeneration of the liver, and changes in blood chemistry and circulating blood cells in laboratory animals. Repeated overexposure to ethylene glycol has the potential to cause similar toxic effects in humans. Ethylene glycol has been shown to cause developmental and reproductive effects at high dose levels in laboratory animals. These findings are of uncertain significance to man. <b>OSHA Regulation 29CFR1910.1000 requires the following permissible exposure limits:</b> a ceiling value of 50 ppm (127 mg/m3) for Ethylene Glycol. <b>The ACGIH recommends the following threshold limit values:</b> a ceiling value of 50 ppm (127 mg/m3) for Ethylene Glycol vapor.							
X-MISCELLANEOUS INFORMATION							
Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary exposure and the removal of the material from eyes, skin and clothing.							
RODUCT CODE NA = NOT AVAILABLE DATE OF ISSUE SUPERSEDES SIGNED 017-0158 O4-21-93 Any previous MSDS							
The information contained herein is based on data considered accurate. However no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained							

thereof. They are offered solely for your consideration, investigation, and verification. Any use of these data and information must be determined by the user to be in accordance with applicable Federal, State and Local laws and regulations. KLEENCO PRODUCTS, INCORPORATED and its Distributors assume no responsibility for personal injury or property damage to vendees, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of the material.