




KLEENCO
FOR QUALITY, VALUE AND PERFORMANCE

KLEENCO PRODUCTS, INC.
• P.O. BOX 1786 • Bellevue, WA. 98009

TELEPHONE NUMBER
Reg. Phone
206-641-8888
For Emergency Assistance
Call Infotrac (800) 535-5053

HAZARD RATING
4 = EXTREME
3 = HIGH
2 = MODERATE
1 = SLIGHT
0 = INSIGNIFICANT
* = SEE SECTION IV



MATERIAL SAFETY DATA SHEET

PRODUCT NAME X-OUT GRAFFITI "EZ"	DATE ISSUED 03-01-93	CODE 0022-0223	DOT HAZARD Flammable NA-1993
FORMULA Proprietary	CHEMICAL NAMES AND OR SYNONYMS Compound Cleaning Liquid	PREPARED BY Dale R. Silbaugh	

I-COMPOSITIONAL INFORMATION/SARA III INFORMATION

INGREDIENTS	CAS NUMBER	OCCUPATION OSHA PEL	EXPOSURE ACGIH TLV	LIMITS OTHER	VAPOR mm Hg	PRESSURE @ TEMP	WEIGHT PERCENT
*Diethylene Glycol n-Butyl Ether	112-34-5	None	None	35PPM	0.1	77°F	31.0

*Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and 40 CFR 342. **NOTE:** The precise composition of this mixture is proprietary. A more complete description will be provided to a physician in the event of a medical emergency.

II - PHYSICAL PROPERTY INFORMATION

APPEARANCE and ODOR Water thin, clear liquid			
MELTING POINT Not Applicable	BOILING POINT 181° to 446°F.	COATING V.O.C. Not Applicable	EVAPORATION RATE Slower than ether
SOLUBILITY IN WATER Complete	SPECIFIC GRAVITY (Water = 1) 0.9	VAPOR DENSITY Heavier than air	

III - FIRE AND EXPLOSION HAZARD INFORMATION

FLASH POINT 53°F. (TCC)	AUTO IGNITION TEMPERATURE Not Available	LOWER EXPLOSION LIMIT (%) 0.9	UPPER EXPLOSION LIMIT (%) 24.6
EXTINGUISHING MEDIA <input checked="" type="checkbox"/> FOAM <input checked="" type="checkbox"/> CO ₂ <input checked="" type="checkbox"/> DRY CHEMICAL <input checked="" type="checkbox"/> WATER SPRAY <input type="checkbox"/> OTHER			
SPECIAL FIRE FIGHTING PROCEDURES For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment. This may include self-contained breathing apparatus to protect against the hazardous effects of normal products of combustion or oxygen deficiency. Read the entire MSDS.			
UNUSUAL FIRE AND EXPLOSION HAZARDS Vapor-air mixtures explosive above flash point. May form explosive peroxides.			

IV - HEALTH HAZARD INFORMATION

THRESHOLD LIMIT VALUE Not Established	ROUTE(S) OF ENTRY: <input checked="" type="checkbox"/> INHALATION See Health Hazards	<input checked="" type="checkbox"/> SKIN See Health Hazards	<input checked="" type="checkbox"/> INGESTION See Health Hazards
HEALTH HAZARDS (Acute and Chronic) CHRONIC EFFECTS OF EXPOSURE for Diethylene Glycol n-Butyl Ether: Repeated inhalation and ingestion can lead to central nervous system and gastrointestinal disturbances. *See Section IX.			
CARCINOGENICITY: Not considered to be a carcinogen <input type="checkbox"/> NTP <input type="checkbox"/> IARC Monographs <input checked="" type="checkbox"/> OSHA Regulated			
SIGNS AND SYMPTOMS OF EXPOSURE INHALATION: Inhalation of vapor may cause respiratory tract irritation, and central nervous system effects including headache, narcosis, weakness, slurred speech and blurred vision. EYE CONTACT: May cause moderate to severe irritation and moderate transient corneal injury depending upon the concentration of the glycol ether. SKIN CONTACT: May cause slight irritation. This material can be absorbed through the skin in acutely toxic amounts. SWALLOWED: May cause irritation of the gastrointestinal tract and central nervous system disturbances.			
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE None Known.			
EMERGENCY AND FIRST AID PROCEDURES EYES: If this chemical contacts the eyes, immediately wash the eyes with large amounts of water, occasionally lifting the lower and upper lids. Get medical attention immediately. Contact lenses should not be worn when working with this chemical. SKIN: If this chemical contacts the skin, flush the contaminated skin with water promptly. If this chemical penetrates the clothing, immediately remove the clothing and flush the skin with water promptly. If irritation persists after washing, get medical attention. INHALATION: If a person breathes large amounts of this chemical, move the exposed person to fresh air at once. If breathing has stopped, perform mouth-to-mouth resuscitation. Keep the affected person warm and at rest. Get medical attention as soon as possible. INGESTION: If this chemical has been swallowed, get medical attention immediately.			

V - REACTIVITY INFORMATION

<input checked="" type="checkbox"/> STABLE	<input type="checkbox"/> UNSTABLE	CONDITIONS TO AVOID None	
HAZARDOUS DECOMPOSITION PRODUCTS May liberate carbon monoxide or carbon dioxide.			
HAZARDOUS POLYMERIZATION	<input type="checkbox"/> MAY OCCUR	<input checked="" type="checkbox"/> WILL NOT OCCUR	CONDITIONS TO AVOID Heat, sparks and open flame.
INCOMPATIBILITY (Materials to avoid) Acids, oxidizing materials.			

VI - SPILL OR LEAK PROCEDURE INFORMATION

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED Stop the source of leak or release. Clean up releases as soon as possible, observing precautions in Special Protective Information. Contain liquid to prevent further contamination of soil, surface water or groundwater. Clean up small spills using appropriate techniques such as sorbent materials or pumping. Where feasible and appropriate, remove contaminated soil. Follow prescribed procedures for reporting and responding to larger releases.	
WASTE DISPOSAL METHODS Place contaminated materials in disposable containers and dispose of in a manner consistent with applicable regulations. Contact local environmental authorities for approved disposal of this material.	

VII - SPECIAL PROTECTION INFORMATION

VENTILATION TYPE	Local mechanical exhaust ventilation, capable of maintaining emissions at the point of use below the PEL.		
RESPIRATORY PROTECTION	Wear a NIOSH-Approved respirator, appropriate for the concentration of vapor or mist encountered at the point of use.		
PROTECTIVE GLOVES	Impervious	EYE PROTECTION	Wear eye protection to prevent any possibility of eye contact.
OTHER PROTECTIVE EQUIPMENT Wear appropriate equipment to prevent any reasonable probability of skin contact.			

VIII - STORAGE AND HANDLING INFORMATION


PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE Keep out of reach of children. Store in a cool dry place away from incompatible materials. Keep container tightly closed when not in use. Workers should wash immediately when skin becomes contaminated. Work clothing should be changed daily if there is any possibility that the clothing may be contaminated. Remove clothing immediately if it is non-impervious clothing that becomes wet. The following equipment should be available: Eyewash, Quick drench. It is generally recognized that contact lenses should not be worn when working with chemicals because contact lenses may contribute to the severity of the injury.	
OTHER PRECAUTIONS Read and follow label instructions. The label contains information necessary for the proper use of the product. Containers, even those that have been emptied, will retain product residue and vapors. Always obey hazard warnings and handle empty containers as if they were full.	

IX - TOXICITY INFORMATION

*HEALTH HAZARDS for Isopropanol: ACUTE HEALTH EFFECTS: INHALATION - Vapors and mists irritate the nose and throat. Inhalation of higher concentrations may cause headaches, vomiting, and coma. Inhalation of very high concentrations or prolonged exposure may cause unconsciousness or death. EYE CONTACT: Vapors will irritate the eyes. Liquid and mists can severely irritate or damage the eyes and cause corneal burns. SKIN CONTACT: Brief contact may dry the skin, or cause burning or stinging sensation. Prolonged or repeated contact may irritate the skin, causing dermatitis. SWALLOWED: Swallowing large quantities causes headaches, nausea, vomiting, stomach cramps and diarrhea, and perhaps unconsciousness, or death. CHRONIC EFFECTS OF EXPOSURE: Prolonged or repeated exposure to high concentrations can produce severe or fatal CNS depression. MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Persons with pre-existing skin disorders, eye problems, or impaired respiratory function may be more susceptible to the effects of this substance.	
--	--

X - MISCELLANEOUS INFORMATION

Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary exposure and the removal of the material from eyes, skin and clothing.	
---	--

PRODUCT CODE 022-0223	NA = NOT AVAILABLE 03-01-93	DATE OF ISSUE	SUPERSEDES 06-31-91	SIGNED 
The information contained herein is based on data considered accurate. However no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained thereof. They are offered solely for your consideration, investigation, and verification. Any use of these data and information must be determined by the user to be in accordance with applicable Federal, State and Local laws and regulations. KLEENCO PRODUCTS, INCORPORATED and its Distributors assume no responsibility for personal injury or property damage to vendees, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of the material.				