



# SAFETY DATA SHEET

Kleenco, Incorporated  
Review Date 18 July, 2016  
Version 1

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

### Product Identifier

Product Name Grease Master  
Product Code 015-0050

Recommended use of the chemical and restrictions on use  
Follow label instructions for proper use.

### Details of the supplier of the safety data sheet

Kleenco Products, Incorporated  
PO Box 1786  
Bellevue, WA 98009  
425-883-2976  
[msds@kleenco.com](mailto:msds@kleenco.com)

### Emergency telephone number

Infotrac  
1-800-535-5053

## 2. HAZARDS IDENTIFICATION

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.122).

OSHA Hazards: Corrosive  
Target Organs: Skin and eyes  
Signal Words: Danger

### Pictograms:



### GHS Classification:

Skin Corrosion/Irritation	Category 1
Serious Eye Damage/Eye Irritation	Category 1
Corrosive to Metals	Category 1

## GHS Label Elements, including precautionary statements:

### Hazard Statements:

May be harmful if swallowed.
Causes severe skin burns and eye damage.
May be corrosive to metals

### Precautionary Statements:

Do not breathe mist, vapors or spray.
Wash hands and exposed skin thoroughly after handling.
Wear protective gloves. Wear eye/face protection. Wear protective clothing.
Keep in original or other corrosion resistant container.

### Response: IMMEDIATELY CALL A POISON CONTROL CENTER OR PHYSICIAN.

<b>Eyes:</b>	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
<b>Skin:</b>	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Wash contaminated clothing before reuse.
<b>Inhalation:</b>	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
<b>Ingestion:</b>	IF SWALLOWED: Rinse mouth. Do not induce vomiting.
<b>Specific Treatment:</b>	See Safety Data Section 4: "FIRST AID MEASURES" for additional information.
<b>Spill:</b>	Absorb spillage to prevent material damage.
<b>Storage:</b>	Store locked up. Store in a corrosion resistant container.
<b>Disposal:</b>	Dispose of contents and container in accordance with local, state and federal regulations.

### Other Information:

Corrosive
Harmful or fatal if swallowed.
Harmful contact may not cause immediate pain.
Harmful if absorbed through skin.
Inhalation of vapors or mist may cause respiratory irritation or damage.
Take off and destroy contaminated shoes.
Keep out of reach of children.
NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS#	Hazardous Components (Chemical Name)	Concentration
7732-18-5	Water	60-100%
111-76-2	2-butoxyethanol	0-10%
1300-72-7	Sodium xylene sulfonate	0-10%
Mixture	Ethoxylated Alcohol	0-10%
1310-73-2	Sodium hydroxide	0-20%

All chemicals above cut off point are listed. Specific chemical identity and/or exact percentage of composition has been withheld as a trade secret.

#### 4. FIRST-AID MEASURES

<b>Eye Contact:</b>	Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IMMEDIATELY CALL A POISON CONTROL CENTER OR PHYSICIAN.
<b>Skin Contact:</b>	Take off immediately all contaminated clothing and shoes. Rinse with water or shower for at least 15 minutes. IMMEDIATELY CALL A POISON CONTROL CENTER OR PHYSICIAN. Wash contaminated clothing before reuse. Discard or destroy contaminated shoes.
<b>Inhalation:</b>	Remove victim to fresh air and keep at rest in a position comfortable for breathing. IMMEDIATELY CALL A POISON CONTROL CENTER OR PHYSICIAN.
<b>Ingestion:</b>	Rinse mouth. Do NOT induce vomiting. IMMEDIATELY CALL A POISON CONTROL CENTER OR PHYSICIAN. Never give anything by mouth to an unconscious person.
<b>Note to Physician:</b>	Probable mucosal damage may contraindicate the use of use of gastric lavage.

#### 5. FIREFIGHTING MEASURES

<b>Suitable (and unsuitable) extinguishing media:</b>	Product does not support combustion, Use extinguishing agent suitable for type of surrounding fire.
<b>Specific hazards arising from the chemical:</b>	Dried product is capable of burning. Combustion products are toxic
<b>Hazardous Combustion Products:</b>	May include Carbon monoxide, Carbon dioxide and other toxic gases or vapors.
<b>Protective Equipment and Precautions for Firefighters:</b>	Wear MSHA/NIOSH approved self-contained breathing apparatus (SCBA) and full protective gear. Cool fire exposed containers with water spray.

#### 6. ACCIDENTAL RELEASE MEASURES

<b>Personal precautions, protective equipment and emergency procedures:</b>	Avoid contact with skin, eyes or clothing. Use personal protective equipment as required.
<b>Environmental precautions:</b>	Do not rinse spill onto the ground, into storm sewers or bodies of water.
<b>Methods and materials for containment and cleaning up:</b>	Prevent further leakage or spillage if safe to do so. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13).

#### 7. HANDLING AND STORAGE

<b>Safe Handling:</b>	Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly after handling.
<b>Storage Conditions:</b>	Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of reach of children. Keep from freezing.
<b>Incompatible Materials:</b>	Reactive metals such as aluminum, zinc and tin. Acids.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits			
Chemical Name	ACGIH TLV	OSHA PEL	NIOSH
2-butoxyethanol 111-76-2	TWA: 20 ppm	TWA 50 ppm. TWA: 240mg/m <sup>3</sup> , (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m <sup>3</sup>	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m <sup>3</sup>
Sodium hydroxide	Ceiling: 2mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup> (vacated) Ceiling: 2mg/m <sup>3</sup>	IDLH: 10 mg/m <sup>3</sup> Ceiling: 2 mg/m <sup>3</sup>
Ethoxylated Alcohol	No exposure limits	No exposure limits	WEEL: 10 mg/m <sup>3</sup>

Engineering Controls:	Provide good general ventilation. If work practices generate dust, fumes, gas, vapors or mists which expose workers to chemicals above the occupational exposure limits, local exhaust ventilation or other engineering controls should be considered. Eye wash stations and shower facilities should be readily accessible in areas where the product is handled.
<b>PERSONAL PROTECTIVE EQUIPMENT</b>	
Eye/Face Protection:	Wear splash goggles. For severe use-conditions, wear a face shield over the goggles.
Skin and Body Protection:	Wear rubber or other chemical-resistant gloves. Use of impervious apron, boots and other protective equipment should be considered in order to prevent or minimize contact with the product.
Respiratory Protection:	Not required with expected use. If occupational exposure limits are exceeded or respiratory irritation occurs, use of a NIOSH/MSHA approved respirator suitable for the use-conditions and chemicals in Section 3 should be considered.
General Hygiene Considerations:	Wash hands and any exposed skin thoroughly after handling. See 29CFR 1910.132-138 for further guidance

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Liquid
Odor	Characteristic
Odor threshold	No data
Color	Green
pH	>13.0
Melting point/freezing point	No data
Initial boiling point and boiling range	~212 F.
Flash point	Not flammable
Evaporation rate	<1 (Butyl acetate =1)
Flammability	Not flammable
Upper/lower flammability or explosive limit	Not explosive
Vapor pressure	No data
Vapor density	No data
Relative density	No data
Solubility	Soluble in water
Partition coefficient n-octanol/water	No data
Auto-ignition temperature	No data
Decomposition temperature	No data

## 10. STABILITY AND REACTIVITY

Reactivity:	This material is considered to be non-reactive under normal conditions of use.
Chemical stability:	Stable under normal conditions.
Possibility of hazardous reactions:	Contact with aluminum or other reactive metals may release hydrogen gas.
Conditions to avoid:	Extremes of temperature and direct sunlight.
Incompatible materials:	Reactive metals such as aluminum, zinc and tin. Acids.
Hazardous decomposition products:	May include carbon monoxide, carbon dioxide (CO <sub>2</sub> ) and other toxic gases or vapors.

## 11. TOXICOLOGICAL INFORMATION

Likely routes of exposure:	Eyes, Skin, Ingestion, Inhalation
<b>Symptoms of Exposure</b>	
Eye Contact:	Pain, redness, swelling of the conjunctiva and tissue damage. Eye contact may cause permanent damage.
Skin Contact:	Pain, redness, blistering and possible chemical burn.
Inhalation:	Irritation or damage to the mucous membranes of the respiratory tract. Nasal discomfort and coughing.
Ingestion:	Damage or chemical burns to mouth, throat and stomach. Pain, nausea, vomiting and diarrhea.
<b>Immediate, Delayed, Chronic Effects</b>	
Product Information:	Data not available or insufficient for classification.
Target Organ Effects:	Blood. Central nervous system. -Eyes. Hematopoietic system. Kidney. Liver. Respiratory System. -Skin.
Carcinogenicity:	No components of this product present at levels greater than or equal to 0.1% are listed as probable, possible or confirmed human carcinogen by ACGIH, IARC, NTP, or OSHA.

Chronic Toxicity	Not available.
Teratogenicity	Not available
Mutagenicity	Not available
Embryotoxicity	Not available
Specific Target Organ Toxicity	Not available

Hazardous Component >1% Acute Toxicity Information			
Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
2-butoxyethanol 111-76-2	470 mg/kg, rat	2270 mg/kg (rat) 220 mg/kg (rabbit)	2.21 mg/L, 4h. (rat) 450 ppm, 4h (rat)
Sodium xylene sulfonate 1300-72-7	7200 mg/kg, rat	No data	No data
Sodium hydroxide 1310-73-2	No data	1350 mg/kg (rabbit)	No data

## 12. ECOLOGICAL INFORMATION

Hazardous Component >1% Acute Ecotoxicity Information				
Chemical Name	Algae/Aquatic Plants	Fish	Toxicity to Microorganisms	Crustacea
2-butoxyethanol 111-76-2	ECO 35 mg/L, 192 h, Microcystis aeruginosa	LC50 1490 mg/L, 96 h, Lepomis macrochirus	EC50 700 mg/L, 16 h, Pseudomonas putida	LC 50 835 mg/L 48 h, Daphnia magna
Sodium xylene sulfonate 1300-72-7	No data	LC50 7960 mg/L, 96 h, Fathead minnow	No data	NOEC 1109 mg/L 7 d, Daphnia magna

Persistence and Degradability	Not Available
Bioaccumulative Potential	Not Available
Mobility in Soil	Not available
PBT and vPvB Assessment	Not Available
Other Adverse Effects	Not Available

## 13. DISPOSAL CONSIDERATIONS

Waste Residues:	Users should review their operations in terms of the applicable federal/national or local regulations and consult with appropriate regulatory agencies if necessary before disposing of hazardous materials or containers.
Product Containers:	Users should review their operations in terms of the applicable federal/national or local regulations and consult with appropriate regulatory agencies if necessary before disposing of hazardous materials product container.

## 14. TRANSPORT INFORMATION

US DOT:	NA1760, Compound Cleaning Liquid (Containing sodium hydroxide), Class 8, PGIII, Corrosive
Special Provisions:	Shipping descriptions may vary based on mode of transport, quantities, package size and/or origin and destination. Limited quantity – Consumer Commodity, ORM-D, DOT-E-173.154. Check with a trained hazardous materials transportation expert for information specific to your situation.

## 15. REGULATORY INFORMATION

TSCA INVENTORY STATUS	All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.
California Proposition 65	Not listed
SARA 302	Not listed
SARA 313	111-76-2
WHMIS Canada	Class E: Corrosive liquid Class D-1B: Material causing other toxic effects (very toxic)

SARA 311/312 Hazard	Yes/No
Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

## 16. OTHER INFORMATION

Revision	Date
Revision 2	09/24/16

**DISCLAIMER:** Kleenco, Incorporated (Kleenco) believes that the information herein is factual but is not intended to be all inclusive. The information relates only to the specific material designated and does not relate to its use in combination with other materials or its use to any particular process. Because safety standards and regulations are subject to change and because Kleenco has no continuing control over the material, those handling, storing or using the material should satisfy themselves that they have current information regarding the particular way the material is handled, stored or used and that the same is done in accordance with federal, national, state and local law. **KLEENCO MAKES NO WARRANTY, EXPRESS OR IMPLIED, INCLUDING (WITHOUT LIMITATION) WARRANTIES WITH RESPECT TO THE COMPLETENESS OR CONTINUING ACCURACY OF THE INFORMATION CONTAINED HEREIN OR WITH RESPECT TO FITNESS FOR ANY PARTICULAR USE.**