

KLEENCO PRODUCTS, INC.
• P.O. BOX 1786 • Bellevue, WA. 98009

TELEPHONE NUMBER Reg. Phone 206-641-8888

For Emergency Assitance
Call Infotrac (800) 535-5053

1 = SLIGHT
0 = INSIGNIFICANT
\* = SEE SECTION IV

HAZARD RATING

4 = EXTREME
3 = HIGH
2 = MODERATE
1 = SLIGHT
0 - INSIGNIFICANT TOXICITY
0

SPECIAL

MATER	IA	L SAFE	ETY	DAT	A S	SHEET		
PRODUCT NAME			DATE ISSU	JED 11-04-9	94	CODE	DOT HAZARD	
SHOWCOTE DURAT	HON	J-V I	PREPARED	Dale R.	Silbaugh	012-0425	Not Regulated	
FORMULA Proprietary	C	CHEMICAL NAMES AND	OR SYNONYM	IS	d Cleaning Liquid		J	
I - COMPOSITIONAL INFORMATION/SARA III INFORMATION								
INGREDIENTS		CAS NUMBER	OCCUPATION OSHA PEL	EXPOUSURE ACGIH TLV	LIMITS OTHER	VAPOR PRESSURE mm Hg @ TEMP	WEIGHT PERCENT	
Dipropylene Glycol Methyl Ether		34590-94-8	100 PPM	100 PPM	150 PPM	0.6 77°F		
No toyle chemical(a) cubicat to the reporting requir	omonto o	footion 212 of Tittle III and 40 C	CD 242 NOTE. The	nradica compos	ition of this mixture	la proprietory A more o	amplete description	
No toxic chemical(s) subject to the reporting requirements of section 313 of Tittle III and 40 CFR 342. <b>NOTE:</b> The precise composition of this mixture is proprietary. A more complete description will be provided to a physician in the event of a medical emergency.								
II - PHYSICAL PROPERTY INFORMATION								
APPEARANCE and ODOR Water thin, milky white liquid								
MELTING POINT	BOILIN	G POINT	COATIN	NG V.O.C.		EVAPORATION	RATE	
Not Applicable SOLUBILITY IN WATER	363° to		\ \\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	Not Applicable DENSITY		Slower than ether		
Complete	SPECIF	IC GRAVITY (Water = 1 1.0	VAPOR	NotApplicable				
III - FIRE AND EXPLOSION HAZARD INFORMATION								
FLASH POINT	AUTO	IGNITION TEMPERATU	RE LOWER	EXPLOSION	LIMIT (%)	UPPER EXPLOS	SION LIMIT (%)	
The state of the s		Not Available		Not Applicable		Not Applic	able	
EXTINGUISHING MEDIA  X FOAM  X CO2  X DRY CHEMICAL  X WATER SPRAY  OTHER								
SPECIAL FIRE FIGHTING PROCEDURES For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment. This may include self-contained breathing apparatus to protect against the hazardous effects of normal products of combustion or oxygen deficiency. Read the entire MSDS.								
UNUSUAL FIRE AND EXPLOSION HAZARDS Noneknown								
IV - HEALTH HAZARD INFORMATION								
THRESHOLD LIMIT VALUE ROUTE		X INHALATION	^	KIN	undo	χ INGESTION	zordo	
Not Established OF ENTRY: See Health Hazards See Health Hazards See Health Hazards  HEALTH HAZARDS (Acute and Chronic) CHRONIC EFFECTS OF EXPOSURE: None known *See Section IX.								
C								
CARCINOGENICITY:	NTP	IARC	C Monographs		HA Regulated			
Not considered to be a carcinogen X								
SIGNS AND SYMPTOMS OF EXPOSURE INHALATION: Vapors and mist can cause the following: -headache - nausea - irritation of nose, throat, and lungs. EYE CONTACT: Direct contact with the material may irritate the eyes. SKIN CONTACT: Prolonged or repeated contact may irritate the skin.								
MEDIAN CONDITIONS OFFICE	00011		N //					
MEDICAL CONDITIONS GENERALLY A	.GGRAV	ATED BY EXPOSURE	None Known.					
EMERGENCY AND FIRST AID PROCE upper lids. Get medical attention if any discomfort skin with water. Where there is evidence of skin in once. Other measures are usually unnecessary.	ritation, d	iet medical attention. INHALA I	HUN: If a person bre	eatnes large amo	unts of this chemi	s of water, occasionally ical contacts the skin, flus cal, move the exposed p	lifting the lower and th the contaminated erson to fresh air at	

V - REACTIVITY INFORMATION
X STABLE UNSTABLE CONDITIONS TO AVOID None
HAZARDOUS DECOMPOSITION PRODUCTS May liberate carbon monoxide or carbon dioxide.
HAZARDOUS MAY WILL NOT CONDITIONS TO AVOID POLYMERZATION OCCUR X OCCUR Heat, sparks and open flame.
INCOMPATIBILITY (Materials to avoid) Acids, oxidizing materials.
VI - SPILL OR LEAK PROCEDURE INFORMATION
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED Stop the source of leak or release. Clean up releases as soon as possible, observing precautions in Special Protective Information. Contain liquid to prevent further contamination of soil, surface water or groundwater. Clean up small spills using appropriate techniques such as sorbent materials or pumping. Where feasible and appropriate, remove contaminated soil. Follow prescribed procedures for reporting and responding to larger releases.
WASTE DISPOSAL METHODS Place contaminated materials in disposable containers and dispose of in a manner consistent with applicable regulations. Contact local environmental authorities for approved disposal of this material.
VII - SPECIAL PROTECTION INFORMATION
VENTILATION TYPE Local mechanical exhaust ventilation, capable of maintaining emissions at the point of use below the PEL.
RESPIRATORY PROTECTION Wear a NIOSH-Approved respirator, appropriate for the concentration of vapor or mist encountered at the point of use.
PROTECTIVE GLOVES Impervious EYE PROTECTION Wear eye protection to prevent any reasonable probability of eye contact.
OTHER PROTECTIVE EQUIPMENT Wear appropriate equipment to prevent any repeated or prolonged skin contact.
VIII - STORAGE AND HANDLING INFORMATION
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE Keep out of reach of children. Store in a cool dry place away from incompatible materials. Keep container tightly closed when not in use. Workers should wash immediately when skin becomes contaminated. Work clothing should be changed daily if there is any possibility that the clothing may be contaminated. Remove clothing immediately if it is non-impervious clothing that becomes wet. The following equipment should be available: Eyewash, Quick drench. It is generally recognized that contact lenses should not be worn when working with chemicals because contact lenses may contribute to the severity of the injury.
OTHER PRECAUTIONS  Read and follow label instructions. The label contains information necessary for the proper use of the product. Containers, even those that have been emptied, will retain product residue and vapors. Always obey hazard warnings and handle empty containers as if they were full.
IX - TOXICITY INFORMATION
*HEALTHHAZARDS for Dipropylene Glycol Methyl Ether: INHALATION: Signs and symptoms of excessive exposure may be anesthetic or narcotic effects. EYE CONTACT: May cause slight transient (temporary) eye irritation: Corneal injury is unlikely. SKIN CONTACT: Prolonged exposure not likely to cause significant skin irritation. SKIN ABSORPTION: The LD50 for skin absorption in rabbits is greater than 20 ml/kg. Prolonged skin contact with very large amounts may cause drowsiness. SWALLOWING: Single dose oral toxicity is low. The oral LD50 for rats is 5.4 ml/kg. Small amounts swallowed incidental to normal handling operations are not likely to cause injury; swallowing amounts larger than that may cause injury. SYSTEMIC (OTHER TARGET ORGAN) EFFECTS: Observations in animals include minor liver or kidney effects. Signs and symptoms of excessive exposure may be anesthetic or narcotic effects.
X - MISCELLANEOUS INFORMATION
Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary exposure and the removal of the material from eyes, skin and clothing.
PRODUCT CODE NA = NOT AVAILABLE DATE OF ISSUE SUPERSEDES SIGNED  012-0425 Any previous MSDS
The information contained herein is based on data considered accurate. However no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained thereof. They are offered solely for your consideration, investigation, and verification. Any use of these data and information must be determined by the user to be in accordance with applicable Federal, State and Local laws and regulations. KLEENCO PRODUCTS, INCORPORATED and its Distributors assume no responsibility for personal injury or property damage to vendees, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of the material.